



FLIR TG54-2™

20:1 Spot IR Thermometer

FLIR TG56-2™

30:1 Spot IR Thermometer with Type K Thermocouple



Key Features:

- Take measurements easily from a safer distance, even in hard-to-reach spots
- Intuitive and user-friendly design with a vivid display
- Bright worklights and laser pointer for precise targeting in

Main Applications:

- Inspecting industrial equipment, both electrical and mechanical
- Monitoring equipment for signs of degradation before it fails
- Ensuring energy efficiency in building inspections

www.flir.com/TG54-2

www.flir.com/TG56-2

SPECIFICATIONS

Model	TG54-2		TG56-2
Imaging and Optical			
Display	1.57" Color EBTN		
Laser Orientation	Single point laser to upper edge of measurement		
Laser Power	<1mW, Class II		
IR Range	-30°C to 850°C (-22°F to 1562°F)		-30°C to 1300°C (-22°F to 2372°F)
Spectral Response	8 μm to 14 μm		
Measurement and Analysis			
AVG	Last 20 readings		
Basic Accuracy	0°C to 100°C (32°F to 212°F): ±1.0°C (±1.8°F)		
Differential (MAX/MIN)	Yes		
Distance to Spot Ratio (D:S)	20:1		30:1
Emissivity	0.01 to 1.00 with 5 presets		
Included Type K Thermocouple Probe Range	—		-30°C to 260°C (-22°F to 500°F)
Input Type	—		K
Input Basic Accuracy	—		±1°C (±1.8°F) or 1% (whichever is greater)
Input Range	—		-30°C to 650°C (-22°F to 1202°F)
Max/Min	Min/Max/Avg/Dif		
Measurement Resolution	0.1°C / 0.1°F		
Response	250 Milliseconds		250 Milliseconds

Model	TG54-2	TG56-2
Power		
Auto Power Off	5 or 15 seconds (selectable)	
Continuous Run Time	8 hours maximum continuous temperature measurements	
Power Source	9V alkaline battery (included)	
General		
Alarm	High/low alarms with programmable set points	
Alarm Alert	HI or LO will flash on the display	
Compatibility	—	Pipe Clamp Probe
Datalogging	Manual and automatic data logger	
Dimensions (L × W × H)	192 mm × 94 mm × 64 mm (7.5 in × 3.7 in × 2.5 in)	192 mm × 125 mm × 64 mm (7.5 in × 4.9 in × 2.5 in)
Includes	Spot IR Thermometer, 9V battery, Quick Start Guide and Storage Pouch	Spot IR Thermometer, 9V battery, Quick Start Guide, Storage Pouch, and Thermocouple
Memory	2 × 99 sets data storage	
Scanning Mode	Yes	
Weight	292 g (10.3 ounces)	310 g (10.9 ounces)
Worklights	Yes	
Environmental and Certifications		
Certifications	CE, UKCA, RCM, WEEE and FDA	
IP Rating	IP65	IP20
Drop Test	3 m (9.8 ft)	1 m (3.2 ft)
Warranty	Limited 3-Year Warranty	

Specifications subject to change. For the most up-to-date specifications, please visit flir.com.

For more information contact: Sales@TeledyneFLIR.com
or to find your local support number, visit: flir.com/contactsupport
www.teledyneflir.com

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2023 Teledyne FLIR, LLC. All rights reserved.

Revised 06/22/23
FLIR_TG54-2_TG56-2_datasheet-LTR-23-0607